

APV A085



PRODUCT NO.: 20201

Serial no.: 504592

Year: 2011

Condition: New

Brand: Pladekøler/plate cooler

Description

SPX Flow Technology Danmark A/S - Drawing no. 2084 1034-2 - Nom. capacity 830 kW -
Transmissionframe 130,4 m² - Working pressure 10,0 Bar - Balanced test pressure 14,3 Bar - Difference
test pressure 12,0 Bar - Volume 193,1 L - Working Temp.: max 95 min 0 grader - CE mark. - plates in
stainless steel.

Gallery

| Model Type | Connection Diameter Inch/Ø | Maximum VR (GPM) | G | W | D | Maximum Plate Length (Inches/Ø) | | Maximum Surface Area (ft²) |
|---------------|----------------------------------|---------------------|---|---|---|------------------------------------|---------|----------------------------------|
| | | | | | | Minimum | Maximum | |
| APV - SR1 | 1.5 | 225 | X | | | 17 | 37 | 132 |
| APV - SR2 | 2.0 | 300 | X | X | X | 30 | 59 | 650 |
| APV - D050 | 3.0 | 450 | X | | X | 16 | 98 | 1800 |
| APV - D055 | 4.0 | 600 | X | | | 40 | 104 | 1900 |
| APV - D055 | 4.0 | 800 | X | | | 40 | 104 | 2800 |
| APV - D080 | 4.0 | 900 | X | | | 40 | 104 | 4200 |
| APV - SR4GH | 4.0 | 800 | X | | X | 40 | 104 | 1400 |
| APV - SR4GL | 4.0 | 800 | X | | | 40 | 104 | 2400 |
| APV - SR4AG | 4.0 | 800 | X | | X | 40 | 104 | 4000 |
| APV - SR4AA | 4.0 | 800 | X | | | 40 | 104 | 4400 |
| APV - L04 | 4.0 | 800 | X | X | | 24 | 98 | 1200 |
| APV - RP | 4.0 | 800 | X | | | 37 | 220 | 3800 |
| APV - D067 | 4.0 | 800 | X | | | 37 | 220 | 4800 |
| APV - A055 | 6.0 | 1800 | X | | | 30 | 98 | 2700 |
| APV - A055 | 6.0 | 1800 | X | | | 30 | 98 | 4100 |
| APV - A445 | 6.0 | 3600 | X | | | 30 | 98 | 9800 |
| APV - SRV | 8.0 | 3100 | X | | | 48 | 138 | 3200 |
| APV - D083 | 8.0 | 3100 | X | | | 39 | 138 | 3800 |
| APV - J022 | 8.0 | 3100 | X | | | 39 | 138 | 6200 |
| APV - J186 | 8.0 | 3100 | X | | | 39 | 138 | 10800 |
| APV - T050N | 8.0 | 3100 | X | X | | 48 | 110 | 9000 |
| APV - T050W | 8.0 | 3100 | X | X | | 48 | 110 | 9700 |
| APV - T050L | 8.0 | 3100 | X | X | | 48 | 110 | 9700 |
| APV - B053 | 12.0 | 7000 | X | X | | 48 | 197 | 8100 |
| APV - B110 | 12.0 | 7000 | X | X | | 48 | 197 | 10800 |
| APV - B134 | 12.0 | 7000 | X | X | | 48 | 197 | 13600 |
| APV - B158 | 12.0 | 7000 | X | X | | 48 | 197 | 15000 |
| APV - B055 | 12.0 | 7000 | X | X | | 48 | 197 | 15800 |
| APV - Z165 | 16.0 | 11,000 | X | | | 147 | 265 | 15000 |
| APV - Z165 | 16.0 | 11,000 | X | | | 147 | 265 | 19100 |
| APV - Z230 | 16.0 | 11,000 | X | | | 147 | 265 | 21000 |
| APV - Z310 | 16.0 | 11,000 | X | | | 147 | 265 | 24200 |
| APV - Z390 | 16.0 | 11,000 | X | | | 147 | 265 | 27000 |
| APV - Z480 | 16.0 | 11,000 | X | | | 147 | 265 | 29000 |
| APV - S100 | 20.0 | 20,000 | X | | | 156 | 250 | 17000 |
| APV - S098 | 20.0 | 20,000 | X | | | 156 | 250 | 20000 |
| APV - S300 | 20.0 | 20,000 | X | | | 156 | 250 | 20000 |
| APV - S090 | 20.0 | 20,000 | X | | | 156 | 250 | 29000 |

- * Wide Gap
- ** 150# ASME Frame
- Design as Basis
- G - Gasketed
- W - Welded Plate Pair
- D - Duo-Safety

