



## OPERATING DATA VOLVO BM A20 6x4

A	mm (ft in)	10044 (32'11")	H	mm (ft in)	1126 (3'8")	O	mm (ft in)	2480 (8'1")	W	mm (ft in)	2490 (8'2")
A <sub>1</sub>	mm (ft in)	5066 (16'7")	H <sub>1</sub>	mm (ft in)	425 (1'5")	P	mm (ft in)	2320 (7'7")	X	mm (ft in)	475 (1'7")
A <sub>2</sub>	mm (ft in)	5537 (18'2")	I	mm (ft in)	1265 (4'2")	Q	mm (ft in)	1500 (4'11")	X*	mm (ft in)	500 (1'8")
B	mm (ft in)	4955 (16'3")	J	mm (ft in)	2394 (7'10")	R	mm (ft in)	397 (1'3")	X <sub>1</sub>	mm (ft in)	627 (2'1")
C	mm (ft in)	3098 (10'2")	J*	mm (ft in)	2450 (8'1")	R*	mm (ft in)	447 (1'5")	X <sub>2</sub>	mm (ft in)	645 (2'1")
C*	mm (ft in)	3123 (10'3")	K	mm (ft in)	1620 (5'3")	R <sub>1</sub>	mm (ft in)	567 (1'2")	Y	mm (ft in)	1954 (6'4")
C <sub>2</sub>	mm (ft in)	1500 (4'11")	K*	mm (ft in)	1676 (5'5")	S	mm (ft in)	1155 (3'9")	Z	mm (ft in)	2492 (8'2")
D	mm (ft in)	2809 (9'2")	L	mm (ft in)	600 (1'11")	T	mm (ft in)	396 (1'3")	a <sub>1</sub>	°	21
E	mm (ft in)	1280 (4'2")	M	mm (ft in)	6350 (20'10")	U	mm (ft in)	3059 (10')	a <sub>2</sub>	°	63
F	mm (ft in)	4322 (14'2")	N	mm (ft in)	7500 (24'7")	U*	mm (ft in)	3115 (10'2")	a <sub>3</sub>	°	45
G	mm (ft in)	1650 (5'4")	N <sub>1</sub>	mm (ft in)	4100 (13'5")	V	mm (ft in)	1928 (6'4")			

\* = unloaded machine

## LOAD CAPACITY Body volumes according to SAE 2:1.

Load capacity	kg	(sh ton)	18500	(20)
Body, struck	m <sup>3</sup>	(yd <sup>3</sup> )	8,7	(11,4)
heaped	m <sup>3</sup>	(yd <sup>3</sup> )	11,0	(14,4)
With underhung tailgate				
body, struck	m <sup>3</sup>	(yd <sup>3</sup> )	9,0	(11,8)
heaped	m <sup>3</sup>	(yd <sup>3</sup> )	11,5	(15,0)